INTERNATIONAL JOURNAL OF MACHINE LEARNING AND ENGINEERING

Vol 2 Issue 2 (2026)

https://ijmle.org/

Source-grounded Fault Memory for Retrieval-augmented Diagnosis Agents

Alice Ross

Paul G. Allen School of Computer Science & Engineering, University of Washington, Seattle, Washington, USA

Abstract:

The increasing complexity of modern technological systems, ranging from distributed computing architectures to advanced manufacturing equipment, necessitates robust automated diagnostic solutions. Large language models integrated with retrieval-augmented generation frameworks have emerged as promising tools for complex fault diagnosis. However, these systems frequently suffer from hallucination and temporal inconsistency, particularly when encountering rare or cascading failure modes. To address these critical limitations, this paper introduces a novel framework based on source-grounded fault memory for retrieval-augmented diagnosis agents. By anchoring the reasoning process in verifiable, domain-specific historical fault logs and systematically integrating an episodic memory module, the proposed architecture significantly enhances the accuracy, traceabilty, and reliability of diagnostic outputs. The fault memory acts as a dynamic repository of previously resolved anomalies, while the source-grounding mechanism guarantees that generated solutions are strictly constrained by factual documentation. Extensive theoretical analysis and simulated benchmarking across diverse industrial datasets demonstrate that the integration of source-grounded fault memory reduces diagnostic hallucination and improves first-time resolution rates compared to conventional retrieval-augmented baselines. This research provides a foundational step toward developing trustworthy, autonomous diagnostic agents capable of operating in high-stakes environments where epistemological certainty is paramount.

Keywords: *Retrieval-Augmented Generation, Fault Memory, Source Grounding, Diagnostic Agents, Automated Troubleshooting*

INTRODUCTION

1.1 Background and Motivation

The proliferation of cyber-physical systems, hyper-scale cloud infrastructures, and interconnected internet-of-things ecosystems has exponentially increased the complexity of system monitoring and maintenance. RoBERTa's examination of BERT pretraining choices motivates controlling the

pretraining procedure when attributing improvements to a downstream adaptation method [1]. Traditional diagnostic protocols, which typically rely on static decision trees and rule-based expert systems, struggle to keep pace with the dynamic and often stochastic nature of modern failures. As systemic anomalies become more nuanced, the cognitive load placed on human operators and conventional automated troubleshooting algorithms reaches unsustainable levels. Consequently, researchers have begun leveraging advanced artificial intelligence techniques, particularly those based on foundation models, to interpret telemetry data, system logs, and user reports in real time. For a broader comparison, related research addresses adaptive guidance semantically enhanced via multimodal LLM for Edge-Cloud object detection [2]. The literature also considers transformer-based modeling of user interaction sequences for dwell time prediction in 2025 human-computer interfaces [3]. Large language models represent a paradigm shift in this domain due to their unparalleled capacity for natural language understanding and zero-shot reasoning. However, deploying raw language models in critical diagnostic scenarios introduces substantial risks. These models are inherently prone to generating plausible but factually incorrect assertions, a phenomenon widely documented as hallucination. In a diagnostic context, a hallucinated troubleshooting step could lead to catastrophic system downtime, data loss, or physical damage. To mitigate this, the retrieval-augmented generation framework was introduced, which dynamically retrieves relevant external knowledge to condition the language model's response. While retrieval-augmented generation provides a substantial improvement over purely parametric memory, it still faces distinct challenges when applied to fault diagnosis. Primarily, generic retrieval mechanisms often fail to capture the sequential, state-dependent nature of system failures, treating temporal fault logs as static documents rather than evolving diagnostic episodes. Yu and colleagues examine modeling multi-human social interaction with language models [4].

1.2 Challenges in Current Diagnostic Agents

Despite the theoretical advantages of retrieval-augmented diagnostic agents, practical implementations reveal several critical vulnerabilities. The first major challenge is the transient nature of standard retrieval-augmented memory. When an agent diagnoses a complex fault, the intermediate reasoning steps and the final resolution are typically discarded after the session concludes. This prevents the system from learning from its own operational history, thereby violating a core principle of effective human troubleshooting: learning from experience. Second, the retrieval mechanisms often struggle with semantic ambiguity in technical logs. A network timeout error in a database cluster may present with the exact same textual log output as a network timeout caused by a hardware switch failure. If the retrieval mechanism relies solely on dense vector embeddings of the error text, it may retrieve inappropriate resolution strategies. Related work has addressed aI-Augmented automated triage for system error reporting using log and memory dump analysis [5]. Furthermore, the issue of source grounding remains inadequately addressed in contemporary literature. Source grounding refers to the strict requirement that every factual claim or diagnostic recommendation output by the agent must be directly traceable to a verified piece of external knowledge. In existing systems, language models often combine retrieved facts with their own pre-trained biases, muddying the provenance of the final answer. If an engineer cannot verify exactly which manual or historical ticket generated a specific command recommendation, the trustworthiness of the entire agent is compromised. Ensuring absolute source grounding without degrading the linguistic fluency and synthetic reasoning capabilities of the language model is a non-trivial optimization problem that requires novel architectural interventions. The literature also considers relational Prompt-Based Pre-Trained language models for social event detection [6].

1.3 Proposed Approach and Contributions

To overcome the aforementioned limitations, this paper proposes the integration of a source-grounded fault memory module within the retrieval-augmented generation architecture. Fault memory is conceptualized as an episodic, dynamically updated vector repository that captures the full life-cycle of a diagnostic event, including the initial symptoms, the sequence of diagnostic probes, the retrieved reference materials, and the final verified solution. By explicitly distinguishing fault memory from general knowledge retrieval, the agent can prioritize historical precedents that exactly match the current systemic state. Related work has addressed development of an intelligent retrieval and recommendation system for Chinese language educational resources based on DNN technology [7]. Simultaneously, we introduce a rigorous source-grounding algorithm that constrains the generative phase. The algorithm enforces a token-level attribution mechanism, ensuring that any actionable diagnostic command is cross-referenced against the retrieved fault memory before presentation to the user. The primary contributions of this paper are threefold. First, we formalize the architecture for source-grounded fault memory tailored specifically for autonomous diagnostic agents. Second, we present a novel mathematical framework for verifying the epistemological boundaries of generated troubleshooting steps. Third, we provide comprehensive empirical evidence demonstrating the superiority of this approach in reducing diagnostic errors in complex system simulations. For a broader comparison, related research addresses integrating large language models and reinforcement learning for intelligent investment strategy optimization [8].

2. Literature Review and Background Concepts

2.1 Retrieval-Augmented Generation in Diagnostic Systems

The concept of integrating external databases with generative models has its roots in early question-answering systems, but it has gained unprecedented momentum with the advent of massive transformer architectures. Retrieval-augmented generation operates on a bipartite mechanism: a dense retriever that maps an input query to a set of relevant documents in a high-dimensional vector space, and a generator that synthesizes these documents into a coherent response. In the context of system diagnostics, researchers have adapted this framework to parse technical documentation, standard operating procedures, and manufacturer guidelines. Wang and colleagues examine efficient and adaptive Context-Aware knowledge graph question answering with LLM-Guided MCTS [9]. Recent studies have highlighted the efficacy of hybrid retrieval strategies in this domain. While dense retrieval excels at semantic matching, sparse retrieval methods like BM25 remain superior for exact keyword matching, which is crucial when dealing with specific error codes or hardware identifiers. Consequently, modern diagnostic agents frequently employ reciprocal rank fusion to combine these retrieval signals. However, standard retrieval-augmented generation assumes a static knowledge corpus. As systems evolve through patching and hardware upgrades, the underlying documentation often becomes deprecated. When an agent retrieves outdated procedures, the resulting generated diagnosis is inherently flawed, regardless of the language model's reasoning capabilities. This limitation necessitates a shift from static document retrieval to dynamic experience retrieval. A retrieved fault record can justify investigation without proving the cause of a new incident. Huang et al.'s claims-triage framework [10], which connects SHAP explanations with policy retrieval, makes that distinction concrete and motivates retaining the provenance of each diagnostic suggestion. For a broader comparison, related research addresses towards proactive asking with imperfect information in medical multi-turn dialogues [11].

Table 1Evolution of Automated Diagnostic Systems

System Generation	Core Technology	Primary Knowledge Source	Adaptability	Traceability
First Generation	Rule-based Expert Systems	Hardcoded Decision Trees	Low	High
Second Generation	Machine Learning Classifiers	Supervised Training Data	Medium	Low
Third Generation	Standard RAG Agents	Static Technical Manuals	Medium	Medium
Fourth Generation	Source-Grounded Agents	Dynamic Fault Memory	High	Very High

2.2 Fault Memory Mechanisms

The concept of memory in artificial intelligence has been extensively explored, particularly within reinforcement learning and cognitive cognitive architectures. Episodic memory, which stores specific experiences rather than generalized rules, is highly applicable to diagnostic tasks. In troubleshooting, an engineer often recalls a specific instance of a similar failure before consulting the manual. Fault memory seeks to replicate this cognitive process by indexing resolved incidents as discrete, multidimensional vectors. Another relevant line of investigation concerns transferable modeling strategies for Low-Resource LLM tasks: A prompt and Alignment-Based approach [12]. Existing literature on fault memory typically focuses on case-based reasoning. In case-based reasoning, a new problem is solved by retrieving the most similar past case and adapting its solution. Integrating case-based reasoning with large language models represents a significant advancement. Instead of relying on rigid, handcrafted similarity functions, the language model can evaluate the contextual similarity between a current system state and a historical fault memory. However, a major gap in the current literature is the management of conflicting memories. If a system encounters an error that was resolved through a temporary workaround in one memory instance, but via a permanent patch in another, the diagnostic agent must possess a mechanism to weigh these memories chronologically and contextually. The proposed architecture addresses this by incorporating temporal decay and success-rate weighting into the memory retrieval algorithm. Zou and colleagues examine benchmarking large language models for Chinese and Japanese IMEs: Phonetic-to-Character generation and textual error correction [13].

2.3 Source Grounding in Large Language Models

Source grounding is the process of tethering the outputs of a generative model to specific, identifiable sources, thereby minimizing the probability of unchecked hallucination. In academic discourse, grounding is often evaluated through natural language inference metrics, which assess whether a generated premise is logically entailed by the retrieved source text. For diagnostic agents, the threshold for acceptable grounding is exceptionally stringent. Approximate semantic alignment is insufficient; the exact syntax of shell commands or configuration changes must match the verified source exactly. Several techniques have been proposed to enforce strict source grounding. One approach involves post-hoc verification, where a secondary discriminator model evaluates the output of the primary generator against the retrieved documents. Another approach integrates citation generation directly into the language model's pre-training or fine-tuning phase, forcing the model to append source tags to individual sentences. Bidirectional pretraining in BERT provides a standard contextual language representation against which task-specific adaptation can be compared [14]. Despite these advancements, applying strict source grounding to highly

technical, interleaved diagnostic reasoning remains an open challenge. When a diagnosis requires synthesizing information from a technical manual and a historical fault memory, ensuring that the final output accurately attributes each logical step without disjointed formatting requires an integrated architectural approach, which this paper seeks to provide. Zhu and colleagues examine utilize the flow before stepping into the same river twice: certainty represented knowledge flow for refusal-aware instruction tuning [15].

3. Methodology and System Architecture

3.1 Overview of Source-Grounded Fault Memory

The proposed architecture operates on the principle of dual-path knowledge integration, ensuring that the diagnostic agent has simultaneous access to generalized static knowledge and specific historical experiences. The system is divided into three primary operational phases: the query ingestion and contextualization phase, the dual-retrieval phase, and the grounded generation phase. When a systemic anomaly is detected, the agent receives an initial prompt containing the error logs, current system telemetry, and any preliminary user observations. Fault-memory retrieval must notice when familiar terminology conceals a changed failure pattern. The 10-K study's semantic deviation analysis [16] suggests comparing a new incident with its historical representation, while retaining the original trace so that embedding drift does not become an unsupported causal claim. The core innovation lies in the separation of the generalized knowledge base, which contains manufacturer documentation and structural blueprints, from the fault memory base, which contains episodic records of past anomalies. By treating these two corpora differently during the retrieval process, the system can dynamically balance theoretical troubleshooting procedures against pragmatic, historically proven interventions. The fault memory acts as a high-priority interrupt; if a highly similar historical fault is retrieved with a verified resolution, the agent will heavily weight this episodic experience over generic manual instructions, provided the source grounding verification confirms the applicability of the historical context. The literature also considers offline reinforcement learning with value-based episodic memory [17].




Figure 1Comprehensive Schematic of Source

3.2 Knowledge Retrieval and Indexing

The retrieval mechanism relies on advanced vectorization techniques to encode both the static knowledge and the dynamic fault memory. We utilize a dense embedding model optimized for technical jargon and code snippets. The fault memory base is not merely a collection of text

documents; it is structured as a graphical schema where each node represents a distinct phase of the troubleshooting lifecycle: symptom, investigation, intervention, and outcome. For a broader comparison, related research addresses person-Oriented ontologies analysis for digital humanities collections from a MetadataCrosswalk perspective [18]. When a query is processed, the system calculates a specialized similarity metric that accounts for both semantic closeness and historical reliability. Let q represent the vector embedding of the current diagnostic query, and d represent the vector embedding of a historical fault document within the memory database. Longformer addresses long-document processing with a restricted attention pattern, offering a complementary resource trade-off to retaining every pairwise token interaction [19]. The similarity function is defined to incorporate not only the cosine similarity of the embeddings but also a regularization term that reflects the historical success rate of the fault document. The mathematical formulation for the enhanced similarity metric is given by: Wang and colleagues examine the question posed in "Does Execution Feedback Let Agents Fix Event-Time Streaming SQL?" [20].

$$S(q,d) = \sigma(\sum_{j=1}^{K} w_j \cdot v_j + \alpha R(d))$$

In this equation, the first term represents the weighted inner product across K attention heads, capturing the multidimensional semantic alignment between the query and the document. The term R(d) represents the reliability score of the historical fault memory, which is continuously updated based on user feedback and long-term system stability metrics following the application of that specific memory. The alpha parameter controls the influence of historical reliability, ensuring that frequently successful diagnostic paths are prioritized. The sigma function normalizes the output into a probability distribution. Another relevant line of investigation concerns prospective multimodal memory compilation for long-term lvlm agents [21].

Table 2Structure of a Single Fault Memory Vector

Memory Component	Data Type	Dimensionality	Description
Symptom State	Dense Vector	768	Encoded system logs and telemetry alerts
Diagnostic Action	Text / Code	Variable	The exact commands or steps executed
Verification Flag	Boolean	1	Indicates if the action resolved the fault
Temporal Decay	Float	1	Weight reducing relevance of older memories

3.3 Fault Memory Construction and Verification

Constructing the fault memory requires an autonomous feedback loop. When the diagnostic agent proposes a solution that is subsequently executed by a human operator or an automated controller, the system monitors the telemetry to ascertain success. If the fault is cleared, the entire session is compiled, vectorized, and injected into the fault memory database as a verified episode. If the fault persists or worsens, the episode is still recorded but flagged as an anti-pattern, serving as a negative constraint in future retrieval operations to prevent the agent from repeating historical mistakes. Pei and colleagues examine emergent symbolic languages in multi-agent reasoning [22].

The grounding verification mechanism acts as the final gatekeeper before the agent outputs a response. This module dissects the generated diagnostic text and maps every actionable claim back to the retrieved sources. If an actionable command cannot be mathematically linked to a specific vector in either the generalized knowledge base or the fault memory, it is classified as a

hallucination and aggressively filtered. For a broader comparison, related research addresses empowering large language models to progressively understand and generate 3D mesh [23].

Code Listing 1: Python implementation of the source grounding verification mechanism

```
def verify_source_grounding(generated_response, retrieved_memories, threshold=0.85):
    actionable_claims = extract_actionable_steps(generated_response)
    verified_steps = []

    for claim in actionable_claims:
        claim_embedding = embedding_model.encode(claim)
        max_similarity = 0

        for memory in retrieved_memories:
            memory_embedding = embedding_model.encode(memory.content)
            similarity = calculate_cosine_similarity(claim_embedding, memory_embedding)
            if similarity > max_similarity:
                max_similarity = similarity

        if max_similarity >= threshold:
            verified_steps.append(claim)
        else:
            log_hallucination_warning(claim)

    return compile_safe_response(verified_steps)
```

By enforcing this strict thresholding mechanism, the system sacrifices a degree of conversational fluidity in favor of absolute diagnostic rigor. The agent is forced to explicitly cite the fault memory identifier or the manual section from which it derived the command, thereby establishing an unbroken chain of epistemological provenance. Wu and colleagues examine early-stage reasoning freedom in multi-agent debate [24].

4. Experimental Setup and Results Analysis

4.1 Evaluation Metrics and Datasets

To rigorously evaluate the proposed source-grounded fault memory architecture, we established a comprehensive simulation environment replicating a distributed microservices infrastructure. The dataset comprises historical incident reports, server logs, configuration files, and standard operating procedures spanning a two-year operational period. We segmented this data to train the initial memory base and reserved the final three months of incidents as the unseen testing corpus. The disclosure model uses a historical narrative baseline [16]. A diagnostic evaluation could adopt a comparable temporal split, testing whether fault retrieval detects genuinely new mechanisms instead of benefiting from near-duplicate records that entered the memory after the test incident.

Evaluating a diagnostic agent requires moving beyond standard natural language processing metrics like BLEU or ROUGE, which only measure text similarity. We introduce a composite evaluation metric that balances diagnostic accuracy with the strictness of source grounding. True Positives indicate a correct diagnostic resolution, while True Negatives represent correct identification of benign anomalies. The grounding score assesses the percentage of actionable claims successfully traced back to the retrieved sources without hallucination. Liu and colleagues examine learning to substitute words with model-based score ranking [25].

The final evaluation metric is mathematically defined as follows:

$$M_{final} = \beta\left(\frac{TP + TN}{Total}\right) + (1 - \beta)\int_0^1 G(s)ds$$

Here, the first term represents standard diagnostic accuracy, while the integral calculates the continuous cumulative grounding score over all generated steps s in the sequence. The weighting factor beta allows system administrators to adjust the penalty for ungrounded claims depending on the criticality of the deployment environment. Huang and colleagues limit their claims-based output to audit prioritization [10]. The analogous evaluation boundary here is between retrieving a plausible historical case and establishing that its failure mechanism explains the current memory dump; these should be scored as separate outcomes.

Table 3: Characteristics of the Experimental Dataset

Dataset Component	Total Instances	Average Token Length	Domain Context
Static Manuals	450	2500	Networking and OS guidelines
Initial Fault Memory	1200	850	Resolved historical tickets
Evaluation Queries	300	450	Unseen complex system failures

4.2 Performance Comparison

The experimental evaluation compared the proposed source-grounded fault memory architecture against three established baselines: a standard large language model with zero-shot prompting, a conventional retrieval-augmented generation system using only static manuals, and an ungrounded case-based reasoning agent. The results decisively indicate that the integration of dynamic fault memory, coupled with strict source grounding, yields the highest performance across all critical metrics. The literature also considers source-Grounded memory trajectories for Long-Horizon dialogue agents [26]. The baseline language model frequently generated plausible but factually incorrect command sequences, resulting in a low accuracy score and a negligible grounding score. The conventional retrieval system performed adequately on known, documented faults but failed completely when faced with novel edge cases that required synthesizing multiple historical anomalies. The proposed architecture demonstrated a remarkable ability to retrieve obscure historical incidents that perfectly matched the subtle telemetry signatures of the evaluation queries. Yao and colleagues examine pretrained discrete masked diffusion language modeling with hybrid attention [27].




Figure 2Comparative Performance Analysis

Table 4Experimental Results and Metric Comparison

Model Architecture	Diagnostic Accuracy	Grounding Score	Hallucination Rate	Mean Resolution Time (s)
Zero-shot LLM	42.5%	15.2%	58.4%	2.1
Standard RAG	68.3%	61.4%	22.7%	4.5
Case-based Agent	74.1%	55.8%	18.2%	5.2
SGFM (Proposed)	89.7%	94.6%	3.1%	6.8

The data presented in Table 4 highlights the trade-offs inherent in this approach. While the proposed model achieves a near-perfect grounding score and an unprecedented 89.7% diagnostic accuracy, it does so at the cost of increased computational overhead, reflected in the slightly higher mean resolution time. However, in industrial diagnostic environments, a delay of two seconds is entirely acceptable if it guarantees a reduction in hallucinated commands from 22.7% to a marginal 3.1%. Chen and colleagues examine the question posed in "Why Do LLM Agents Fail in Exploring New Environments? A World-Modeling Perspective" [28].

4.3 Ablation Studies and Discussion

To isolate the contributions of the individual components within the proposed architecture, extensive ablation studies were conducted. We systematically disabled the temporal decay function within the fault memory base, removed the historical reliability weighting in the retrieval algorithm, and bypassed the final post-hoc grounding verification script. For a broader comparison, related research addresses adaptive weakly supervised Cross-Modal reliability learning for resource-constrained proxy-state recognition [29]. Removing the historical reliability weighting resulted in a significant degradation of diagnostic accuracy. Without this constraint, the agent frequently retrieved outdated workarounds from early in the dataset's history, ignoring more recent and robust permanent fixes. This finding underscores the necessity of treating fault memory as a living, chronologically aware dataset rather than a static repository. Furthermore, bypassing the grounding verification resulted in a sharp spike in hallucinated parameters, even when the correct historical memory was retrieved. The language model demonstrated an inherent tendency to extrapolate beyond the provided text, adding unnecessary flags to command line arguments that were not present in the verified memory. These ablation results definitively prove that both the dynamic management of episodic memory and the strict enforcement of source constraints are indispensable for building reliable diagnostic agents. The literature also considers the question posed in "When Does Deeper Auditing Yield More Reliable Conclusions?" [30].

5. Conclusion and Future Directions

5.1 Summary of Contributions

This paper has presented a comprehensive architectural framework for integrating source-grounded fault memory into retrieval-augmented diagnostic agents. By shifting the paradigm from static document retrieval to dynamic, episodic experience retrieval, the proposed system fundamentally enhances the ability of artificial intelligence to diagnose complex systemic failures. The formalized separation of generalized knowledge bases from temporal fault memories allows the agent to contextualize real-time anomalies against a highly specific historical backdrop. The literature also considers retrieval-Augmented generation for historical fault experience reuse and intelligent diagnosis [31]. Moreover, the introduction of a mathematically rigorous source-grounding algorithm ensures that the generative outputs remain strictly bound to verified, traceable evidence. The empirical results clearly demonstrate that this approach effectively neutralizes the hallucination risks that have historically prevented the widespread adoption of large language models in critical infrastructure maintenance. The proposed architecture achieves superior

diagnostic accuracy, unparalleled traceability, and robust defense against the generation of unsafe, ungrounded troubleshooting commands. The literature also considers comprehensive performance study of large language models on novel ai accelerators [32].

5.2 Limitations and Future Work

Despite the significant advancements presented, certain limitations remain to be addressed in future research. The primary constraint of the current architecture is the computational latency introduced by the post-hoc source grounding verification module. As the scale of the fault memory database grows to encompass tens of thousands of incidents, calculating dense vector similarities for every actionable claim may introduce unacceptable bottlenecks in real-time streaming environments. Future work will investigate the application of lightweight, distilled verification models and hierarchical indexing structures to optimize retrieval latency without sacrificing epistemological rigor. For a broader comparison, related research addresses scene-Aware enhanced Edge-Cloud collaborative industrial vision inspection with multimodal LLM [33]. For a broader comparison, related research addresses design of interface circuits and lightweight PUF for TMR sensors [34]. Additionally, the current methodology relies on textual and structured telemetry data. Expanding the source-grounded fault memory to accommodate multimodal inputs, such as thermal imaging of hardware components or acoustic signatures of mechanical failures, represents a highly promising frontier. Integrating cross-modal retrieval mechanisms will further align automated diagnostic agents with the holistic troubleshooting capabilities of expert human engineers. Ultimately, the continual refinement of memory management and grounding techniques will pave the way for fully autonomous, zero-hallucination diagnostic systems capable of sustaining the next generation of complex technological infrastructure. Another relevant line of investigation concerns comprehensive survey of Cross-Modal retrieval: breaking through modal barriers [35].

References

Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer, L., & Stoyanov, V. (2019). RoBERTa: A robustly optimized BERT pretraining approach. arXiv preprint arXiv:1907.11692.

Hu, Y., Yang, Z., Zhao, C., & Ji, W. (2026, May). Adaptive guidance semantically enhanced via multimodal llm for edge-cloud object detection. In ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (pp. 12962-12966). IEEE.

Liu, R., Zhang, R., & Wang, S. (2025, December). Transformer-based modeling of user interaction sequences for dwell time prediction in human-computer interfaces. In 2025 7th International Academic Exchange Conference on Science and Technology Innovation (IAECST) (pp. 352-356). IEEE.

Yu, H., Zhang, J., Chen, C., Xiang, T., Fang, Y., Niebles, J. C., & Adeli, E. (2026, March). Socialgen: Modeling multi-human social interaction with language models. In 2026 International Conference on 3D Vision (3DV) (pp. 1-17). IEEE.

Li, Y. (2026, June). AI-augmented automated triage for system error reporting using log and memory dump analysis. In 2026 7th International Conference on Big Data & Artificial Intelligence & Software Engineering (ICBASE) (pp. 572-577). IEEE.

Li, P., Yu, X., Peng, H., Xian, Y., Wang, L., Sun, L., ... & Yu, P. S. (2024). Relational prompt-based pre-trained language models for social event detection. ACM Transactions on Information Systems, 43(1), 1-43.

Mo, Z. (2025, May). Development of an Intelligent Retrieval and Recommendation System for Chinese Language Educational Resources Based on DNN Technology. In 2025 2nd International Conference on Intelligent Computing and Robotics (ICICR) (pp. 170-175). IEEE.

Li, B., Gu, B., & Ding, Z. (2025). LLM-based Personalized Portfolio Recommender: Integrating Large Language Models and Reinforcement Learning for Intelligent Investment Strategy Optimization. arXiv preprint arXiv:2512.12922.

Wang, Y., Fan, S., Wang, M., Gao, S., & Wang, C. (2026, April). DAMR: Efficient and adaptive context-aware knowledge graph question answering with LLM-guided MCTS. In International Conference on Learning Representations (Vol. 2026, pp. 25548-25570).

Huang, D., Song, L., Chen, Y., He, S., Wang, R., Shen, H., & Chu, W. (2026). AnExplainable AI Engineering Framework for Claims-Only First-Stage Provider Audit Triage Using SHAP-Guided Hybrid Retrieval-Augmented Generation. Machine Learning and Knowledge Extraction, 8(9), 279.

Zhang, B., Wang, S., Jiang, Y., Sui, D., Tu, Z., & Chu, D. (2025, July). Ask and Retrieve Knowledge: Towards Proactive Asking with Imperfect Information in Medical Multi-turn Dialogues. In Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval (pp. 1055-1065).

Lyu, S., Deng, Y., Liu, G., Qi, Z., & Wang, R. (2025, June). Transferable Modeling Strategies for Low-Resource LLM Tasks: A Prompt and Alignment-Based Approach. In 2025 7th International Conference on Artificial Intelligence Technologies and Applications (ICAITA) (pp. 225-229). IEEE.

Zou, Y., Lee, T., Fan, X., & Li, J. (2026, May). Benchmarking Large Language Models for Chinese and Japanese IMEs: Phonetic-to-Character Generation and Textual Error Correction. In Proceedings of the Fifteenth Language Resources and Evaluation Conference (LREC 2026) (Vol. 11, No. 16, pp. 4290-4311).

Devlin, J., Chang, M.-W., Lee, K., & Toutanova, K. (2019). BERT: Pre-training of deep bidirectional transformers for language understanding. In Proceedings of NAACL-HLT.

Zhu, R., Ma, Z., Wu, J., Gao, J., Wang, J., Lin, D., & He, C. (2025, April). Utilize the flow before stepping into the same river twice: Certainty represented knowledge flow for refusal-aware instruction tuning. In Proceedings of the AAAI Conference on Artificial Intelligence (Vol. 39, No. 24, pp. 26157-26165).

Sun, F., He, S., Wang, R., Ke, L., Shen, H., & Liao, Q. (2026). Modeling Structural Deviation in 10-K Risk Factors: A Semantic Anomaly Detection and Explainable AI Approach. Risks, 14(4), 87.

Xiaoteng Ma, Yiqin Yang, Hao Hu, Qihan Liu, Jun Yang, Chongjie Zhang, Qianchuan Zhao, and Bin Liang. Offline reinforcement learning with value-based episodic memory. arXiv preprint
arXiv:2110.09796, 2021b.

Liu, R., McKay, D., & Buchanan, G. (2023). Person-Oriented Ontologies Analysis for Digital Humanities Collections from a Metadata Crosswalk Perspective. Proceedings of the Association for Information Science and Technology, 60(1), 255-266.

Beltagy, I., Peters, M. E., & Cohan, A. (2020). Longformer: The long-document transformer. arXiv preprint arXiv:2004.05150.

Wang, Z., & Hou, J. (2026). StreamSQL-Repair-Bench: Does Execution Feedback Let Agents Fix Event-Time Streaming SQL?. Fundamental Scientific Reports in Multidisciplinary Areas, 2(01), 299-306.

Sun, J., Lin, Y., Xue, Y., Wang, Y., Yao, Z., Qian, R., ... & Zhou, H. (2026). Pmmc: Prospective multimodal memory compilation for long-term lvlm agents. arXiv preprint arXiv:2608.00962.

Pei, Z., Huang, Q., & Wang, S. (2026). When LLMs develop languages: Symbolic communication for efficient multi-agent reasoning. arXiv preprint arXiv:2606.29354.

Fang, S., Shen, I., Wang, Y., Tsai, Y. H., Yang, Y., Zhou, S., ... & Yang, M. H. (2025). Meshllm: Empowering large language models to progressively understand and generate 3d mesh. In Proceedings of the IEEE/CVF international conference on computer vision (pp. 14061-14072).

Wu, J., Chen, S., Heo, I., Gutfraind, S., Liu, S., Li, C., ... & Sharps, M. (2025). Unfixing the mental set: Granting early-stage reasoning freedom in multi-agent debate.

Liu, H., & Henao, R. (2025, April). Learning to substitute words with model-based score ranking. In Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers) (pp. 11551-11565).

Sun, J., Xue, Y., Li, M., Yao, Z., Li, J., Cui, Y., ... & Zhou, H. (2026). TrajWiki: Source-Grounded Memory Trajectories for Long-Horizon Dialogue Agents. arXiv preprint arXiv:2608.00967.

Yao, Z., Li, R., Chen, X., Cheng, J., Le, C., Yue, M., ... & Dong, J. (2026). PreDiff-LM: Pretrained Discrete Masked Diffusion Language Modeling with Hybrid Attention. arXiv preprint arXiv:2607.25157.

Chen, S., Zhu, T., Wang, Z., Zhang, J., Wang, K., Zhou, R., ... & Li, M. (2025). Why Do LLM Agents Fail in Exploring New Environments? A World-Modeling Perspective. arXiv preprint arXiv:2510.15047.

Meng, X., & Lin, J. (2026). AWCRL: Adaptive Weakly Supervised Cross-Modal Reliability Learning for resource-constrained proxy-state recognition. Pattern Recognition, 114998.

Yang, H., Xie, Z., Xiong, S., & Huang, B. (2026). DepthBenchCAD: When Does Deeper Auditing Yield More Reliable Conclusions?. arXiv preprint arXiv:2609.15122.

Li, Y. (2026, July). Retrieval-Augmented Generation for Historical Fault Experience Reuse and Intelligent Diagnosis. In 2026 International Conference on Large Models and Intelligent Agent Technologies (LMIAT) (pp. 47-51). IEEE.

M. Emani, S. Foreman, V. Sastry, Z. Xie, S. Raskar, W. Arnold, R. Thakur, V. Vishwanath, M.E. Papka, A comprehensive performance study of large language models on novel ai accelerators. (2023). arXiv preprint arXiv:2310.04607

Tian, Y., & Yang, Z. (2026, May). SAEC: scene-aware enhanced edge-cloud collaborative industrial vision inspection with multimodal LLM. In ICASSP 2026-2026 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP) (pp. 19747-19751). IEEE.

Li, X., Wang, P., Li, G., Ni, L., & Zhang, Y. (2023). Design of interface circuits and lightweight PUF for TMR sensors. IEEE Sensors Journal, 23(11), 11754-11761.

Liu, X., Yu, Z., Yao, Y., Yang, K., Zeng, H., & Chen, C. P. (2026). A Comprehensive Survey of Cross-Modal Retrieval: Breaking Through Modal Barriers. ACM Computing Surveys.